Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Luxform

Supplier's address: Luxform Global BV, Transportstraat 1, 8263BW Kampen, NL

Model identifier: 97171

Type of light source:

| Lighting technology used: | LED | Non-directional or directional: | NDLS | | | |
|-------------------------------|------|---------------------------------|------|--|--|--|
| Light source cap-type | N/a | | | | | |
| (or other electric interface) | | | | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No | | | |
| Colour-tuneable light source: | No | Envelope: | - | | | |
| High luminance light source: | No | | | | | |
| Anti-glare shield: | Yes | Dimmable: | No | | | |
| Product parameters | | | | | | |

| | | Flouuct para | lieters | | | |
|--------------------------------------|--|------------------------|---|-----------------------|--|--|
| Parameter | | Value | Parameter | Value | | |
| General product parameters: | | | | | | |
| | mption in on- 000 h), rounded est integer | 2 | Energy efficiency class | G | | |
| indicating if it i in a sphere (3 | us flux (φuse), refers to the flux 60º), in a wide in a narrow cone | 11 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 25002900 | | |
| On-mode expressed in W | power (P _{on}), | 1,4 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | | |
| for CLS, expre | ndby power (P _{net}) essed in W and second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set | 80 | | |
| Outer dimensions without | Height | 50 | Spectral power | See image | | |
| | Width | 10 000 | distribution in the | in last page | | |
| | Depth | 133 | 1 | Page 1 / 3 | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | | | | |
|--|------|---|-------|--|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity | 0,461 | | | |
| | | coordinates (x and y) | 0,416 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 80 | Survival factor | 1,00 | | | |
| the lumen maintenance factor | 0,60 | | | | | |
| (a) | | 1 | | | | |

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

